

SUPERCLOSER SC400

POLYBAG-IN-BOX DECUFFER FOLDER CLOSER



The Supercloser SC400 mechanically un-cuffs a bag in a box clear of the case flaps, opens the side flaps and folds the bag into a neat two-way fold to protect the filled product.





TECHNICAL SPECIFICATIONS SUPERCLOSER SC400:

Case range:	Supercloser SC400
8' (2.4 meter) machine:	10.00" x 8.00" x 6.00" / 250mm x 200mm x 150mm (L x W x H) min.
10' (3 meter) machine:	16.00" x 14.00" x 16.00" / 400mm x 350mm x 400mm (L x W x H) max.
10' (3 meter) optional:	20.00" x 14.00" x 16.00" / 500mm x 350mm x 400mm (L x W x H) max.
10' (3 meter) optional:	24.00" x 16.00" x 16.00" / 600mm x 400mm x 400mm (L x W x H) max.
Speed:	Up to 10 -15 cases per min. depending on case size
Bag materials:	All standard polyethylene films (HDPE, LDPE, LLDPE, co-extrusions)
Bag gauges:	1.0 - 4.0 mil depending on material.
Pneumatic:	80-100 psi, 1/2" supply.
Finish:	Stainless steel frame, covers, contact parts and electrical enclosure. Internal components stainless steel, aluminum or plated.
Machine handling:	Right to left or left to right to requirement.

FEATURES

Stainless steel finish.	Clean and durable, maintains hygiene.
Heavy duty indexing conveyor.	Highest speed at low maintenance.
In-feed gate.	Separates cases for automatic operation.
Opens the side flaps.	More positive folding process.
Fully interlocking guarding.	Operator safety and OSHA compliance.

BENEFITS

SUPERCLOSER SC400 OPTIONS:

- Automatic case sealer.
- Tamper.
- Bag top heat seal assembly.
- Smaller or larger case sizes.



OK International Corporation
 73 Bartlett Street
 Marlborough, MA 01752
 USA
 Phone: 1-508-303-8286
 Fax: 1-508-303-8207
 sales@okcorp.com